NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9120621
Type of light source: LED



Product information Sheet

General Information

Material number	**9120621**
Type	**Wall light**
Product segment	**Outdoor**

Dimensions

Length (in cm)	**14.5 Cm**
Width (in cm)	**16.2 Cm**
Height (in cm)	**24 Cm**
Net Weight	

Material & Colour

Enclosure Material	**Die-Casting Aluminium & Acrylic Diffuser**
Colour	**Anthracite**
Adjustable	

Functionality

Switch Type	**Switch On/Off ,Solar & Sensor**
Function	
Battery	
USB Charger	

Technical Information

Protection Degree	**IP65**
Protection Class	**CLASS III**
Mains Voltage	**220V**
max. Wattage	**2 W**
Lumen	**100.13 Lm**
Equivalence With Incandescent Lamp (W)	
Colour Temperature	**3000K**
Nominal Lifetime (in h)	**30000H**
Switching Cycles	**-**
Colour Rendering Index (Ra, CRI)	**>80**
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	Yes
Anti-glare shield [yes/no]	Yes
Dimmable [yes/only with specific dimmers/no]	Yes

General Product parameters

Energy consumption in on-mode (kWh/1000h)	2
Energy efficiency class	
Useful luminus flux (Φ_{use}), indicating if it refers to the flux in a sphere (360˚), in a wide cone (120˚) or in a narrow cone (90˚)	
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	
On-mode power (P_{on}), expressed in W [x,x]	
Standby power (P_{sb}), expressed in W and rounded to the second decimal	
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distri bution in the range 250 nm to 800 nm, at full-load	
Chromaticity coordinates (x and y)	
Peak luminous intensity (cd)	125º
Beam angle in degrees, or the range of beam angles that can be set	

Parameters for LED and OLED light sources

R9 colour rendering index value	
Survival factor [x,xx]	
The lumen maintenance factor [x,xx]	
Displacement factor (cos φ1)	
Colour consistency in McAdtam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x	
Stroboscopic effect metric (SVM) [X,X	
Pon in W	
Displacement factor (cos φ1) for LED and OLED mains light sources	
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	
Flicker metric (PstLM) for LED and OLED light sources	
Stroboscopic effect metric (SVM) for LED and OLED light sources	
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	