NOVA LUCE

**Supplier's name or trade mark:** NOVA LUCE S.A
**Supplier's address:** SCHIMATARI VIOTIAS 32009, GREECE
**Model identifier:** 9060914
**Type of light source:** LED



# Product information Sheet

## General Information

| | |
|---|---|
| **Material number** | **9060914** |
| **Type** | **Wall light** |
| **Product segment** | **INDOOR** |

## Dimensions

| | |
|---|---|
| **Length (in cm)** | **90 Cm** |
| **Width (in cm)** | **2.7 Cm** |
| **Height (in cm)** | **7.5 Cm** |
| **Net Weight** | |

## Material & Colour

| | |
|---|---|
| **Enclosure Material** | **Aluminium** |
| **Colour** | **Sandy White** |
| **Adjustable** | **No** |

## Functionality

| | |
|---|---|
| **Switch Type** | **No** |
| **Function** | **LED PHILIPS SMD** |
| **Battery** | **No** |
| **USB Charger** | **No** |

## Technical Information

| | |
|---|---|
| **Protection Degree** | **IP44** |
| **Protection Class** | |
| **Mains Voltage** | **230V** |
| **max. Wattage** | **36W** |
| **Lumen** | **2614Lm** |
| **Equivalence With Incandescent Lamp (W)** | |
| **Colour Temperature** | **3000K** |
| **Nominal Lifetime (in h)** | **30000H** |
| **Switching Cycles** | **-** |
| **Colour Rendering Index (Ra, CRI)** | **CRI >90** |
| **Rated Lamp Power (0,1W precision)** | **-** |
| **Colour Tolerance (LED, SDCM)** | |

## Product information

| | |
|---|---|
| Lighting technology used [LED/OLED/MIXED/OTHER] | LED |
| Non-directional or directional [NDLS/DLS] | |
| Mains or non-mains [MLS/NMLS] | |
| Connected light source (CLS) [yes/no] | |
| Colour-tuneable light source [yes/no] | |
| Envelope [no/second/non-clear] | |
| High luminance light source [yes/no] | |
| Anti-glare shield [yes/no] | |
| Dimmable [yes/only with specific dimmers/no] | No |

## General Product parameters

| | |
|---|---|
| Energy consumption in on-mode (kWh/1000h) | 11k |
| Energy efficiency class | F |
| Useful luminus flux ($\Phi_{use}$), indicating if it refers to the flux in a sphere (360˚), in a wide cone (120˚) or in a narrow cone (90˚) | |
| Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set : | 3000K |
| On-mode power ($P_{on}$), expressed in W [x,x] | |
| Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | |
| Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set | |
| Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre): | |
| Spectral power distri bution in the range 250 nm to 800 nm, at full-load | |
| | |
| Claim of equivalent power (c) | |
| If yes, equivalent power (W) | |
| Chromaticity coordinates (x and y) | |

## Parameters for directional light sources

| | |
|---|---|
| Peak luminous intensity (cd) | |
| Beam angle in degrees, or the range of beam angles that can be set | |

## Parameters for LED and OLED light sources

| | |
|---|---|
| R9 colour rendering index value | |
| Survival factor [x,xx] | |
| The lumen maintenance factor [x,xx] | 70% |
| Displacement factor (cos φ1) | |
| Colour consistency in McAdam ellipses | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage | |
| If yes then replacement claim (W) | |
| Flicker metric (Pst Lm) [x,x] | |
| Stroboscopic effect metric (SVM) [X,X] | |
| Pon in W | |



Contact | Support
www.novaluce.com