NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9492580
Type of light source: LED



Product information Sheet

General Information

Material number	**9492580**
Type	**Table**
Product segment	**OUTDOOR**

Dimensions

Length (in cm)	**11Cm**
Width (in cm)	**6Cm**
Height (in cm)	**11Cm**
Height 2 (in cm)	
Cut Out (in cm)	
Net Weight	**650Kg**

Material & Colour

Enclosure Material	**Die-casting Aluminum & Glass**
Colour	**Anthracite**
Adjustable	

Functionality

Switch Type	
Function	
Battery	**No**
USB Charger	**No**


Technical Information

Protection Degree	**IP65**
Protection Class	**I**
Mains Voltage	**220-240V**
max. Wattage	**8W**
Lumen	**188**
Equivalence With Incandescent Lamp (W)	**-**
Colour Temperature	**3000K**
Nominal Lifetime (in h)	**20000H**
Switching Cycles	
Colour Rendering Index (Ra, CRI)	**81**
Rated Lamp Power (0,1W precision)	**7.7W**
Colour Tolerance (LED, SDCM)	**5.2**

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	MLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	8k
Energy efficiency class	G
The calculations performed with the parameters,including the determination of the energy class	
Useful luminus flux (Φ_{use}), indicating if it refers to the flux in a sphere (360˚), in a wide cone (120˚) or in a narrow cone (90˚)	242lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3100K
On-mode power (P_{on}), expressed in W [x,x]	8W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	82
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	Complete light
Spectral power distri bution in the range 250 nm to 800 nm, at full-load	
Claim of equivalent power (℃)	No
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	222
Beam Angle in degrees for directional light sourrce	
Stanby Power (Psb) in W	0
UGR	<25.9
Networked standby power (Pnet) in W for connected light sources (CLS)	0

Parameters for LED and OLED light sources

R9 colour rendering index value	9
Survival factor [x,xx]	100%
The lumen maintenance factor [x,xx]	98%
Displacement factor (cos φ1) for LED and OLED mains light sources LED/OLED	0,962
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	5,2
Flicker metric (PstLM) for LED and OLED light sources	0,041
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,051
Pon in W	

Contact | Support
www.novaluce.com