NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 5231301
Type of light source: LED



Product information Sheet

General Information

Material number	5231301
Type	Fan
Product segment	INDOOR

Dimensions

Diameter (in cm)	132 Cm
Width (in cm)	- Cm
Height (in cm)	32-45 Cm
Blade Sweep	52''
Net Weight	4,8 Kg

Material & Colour

Enclosure Material	Steel
Blades Material	Walnut Wood
Colour	Matt Black
Blades	Wood, 3pcs

Functionality

Speed	5 Speed Remote
Function	-
Summer/winter function	Yes
Length of Each Blade	66 cm
Motor Type	DC
Airflow (CFM)	4000
RPM	200
Noise Level	< 30dB
Light	No
Remote Control	Yes
Guarantee	5 years

Technical Information

Protection Degree	IP20
Protection Class	I
Power Supply	AC110-240V
max. Wattage	40W
Motor DC Watt	26W
LED Watt	18W
Max. Airflow CFM	5000CFM
Lumen	650Lm

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	-
Non-directional or directional [NDLS/DLS]	
Mains or non-mains [MLS/NMLS]	
Connected light source (CLS) [yes/no]	
Colour-tuneable light source [yes/no]	-
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	-
Anti-glare shield [yes/no]	-
Dimmable [yes/only with specific dimmers/no]	-

General Product parameters

Hourly consumption (KWH)	0,026
Noise level	<50DB
Useful luminus flux (Φ_{use}), indicating if it refers to the flux in a sphere (360˚), in a wide cone (120˚) or in a narrow cone (90˚)	
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	
Standby power (P_{sb}), expressed in W and rounded to the second decimal	
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any Height/Width /Depth:	-
Spectral power distri bution in the range 250 nm to 800 nm, at full-load	-
Claim of equivalent power (c)	
If yes, equivalent power (W)	-
Chromaticity coordinates (x and y)	

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	160º

Parameters for LED and OLED light sources

R9 colour rendering index value	
Survival factor [x,xx]	-
The lumen maintenance factor [x,xx]	-
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	-
Pon in W	
Beam Angle in degrees for directional light source	
Stanby Power (Psb) in W	
Displacement factor (cos φ1) for LED and OLED mains light sources	-
Flicker metric (PstLM) for LED and OLED light sources	-

Contact | Support
www.novaluce.com